


**M**andrino cambio rapido a doppia compensazione.


**Q**uick-coupling spindle with double compensation.


**Caratteristiche generali / Technical data**


TIPO BUSSOLA / BUSH TYPE		1	2	3
ø I (mm)		19	31	48
ø E (mm)		37	53,5	79
Compensazione / Compensation	Trazione / Pull	7	12	20
	Press. / Push	8	13	20

**2**
**Mod. DIN 228B**


Tipo bussola / Bush type	1		2		3	
Per filettature / For threading	M 2 ÷ M 12		M 6 ÷ M 20		M 12 ÷ M 33	
Cono Morse / Taper	CM 2	CM 3	CM 3	CM 4	CM 4	CM 5
L 1 (mm)	37	37	72,5	74	107	107
Peso / Weight (Kg)	0,25	0,4	0,8	1,2	2,45	3,0
<b>CODICE / CODE</b>	<b>91100</b>	<b>91200</b>	<b>92100</b>	<b>92200</b>	<b>93100</b>	<b>93200</b>

**Mod. DIN 228A**


Tipo bussola / Bush type	1		2		3	
Per filettature / For threading	M 2 ÷ M 12		M 6 ÷ M 20		M 12 ÷ M 33	
Cono Morse / Taper	CM 2	CM 3	CM 3	CM 4	CM 4	CM 5
L 1 (mm)	37	37	72,5	74	107	107
Peso / Weight (Kg)	0,3	0,45	0,85	1,3	3,5	3,3
<b>CODICE / CODE</b>	<b>91300</b>	<b>91400</b>	<b>92300</b>	<b>92400</b>	<b>93300</b>	<b>93400</b>

**Mod. DIN 1835**


Tipo bussola / Bush type	1	2
Per filettature / For threading	M 2 ÷ M 12	M 6 ÷ M 20
ø F (mm)	25	25
L 1 (mm)	41	67,5
L 2 (mm)	56	56
Peso / Weight (Kg)	0,45	0,75
<b>CODICE / CODE</b>	<b>91500</b>	<b>91600</b>

A richiesta si costruiscono attacchi speciali / Special connectors are manufactured on request.